



OFTEN COPIED / NEVER EQUALED™
SINCE 1958

LIFTING EYE SERIES

These models are engineered and designed for the transporting and lifting of cylinders. Features include a **5 to 1** lifting safety ratio, heavy-duty steel frame construction, large slotted locking tool box, our exclusive fast action cylinder placement bands and a heavy gauge reinforced toeplate.

NO.94L-16S

HEIGHT: 64" WIDTH: 37" (O.D.)
WEIGHT: 106 lbs.

WHEEL NO: W-17SP
(16" SOLID RUBBER)

CYLINDER CAPACITY:

244 TO 330 CU.FT. OXYGEN
AND
(NO.4.5 - NO.5 - WK) ACET. OR 100 lb.
PROPANE CYLINDERS

**CANTILEVERED
LIFTING EYE**

**(TO HELP KEEP LOAD
BALANCED WHEN LIFTED)**

5 TO 1 LIFTING SAFETY RATIO

**LARGE LOCKING
TOOLBOX**

**HEAVY GAUGE
ANGLE IRON FRAME**

**FAST ACTION CYL.
PLACEMENT BANDS**

**HEAVY-GAUGE
TOEPLATE**

**16" SOLID RUBBER TIRES
SECURED WITH LOCKNUTS
(NO COTTER PINS)**



1.877.721.7211
WWW.ANTHONYCARTS.COM